### **PRODUCT FEATURES**



# LAMPING

Turnbuckles and anchors can be mounted to the walls or ceiling. When ceiling mounting kit, cables will drop 2" below ceiling. Includes five highly adjustable Accent heads (20 Watts max each) that tilt between the cables and rotate 120° within their rings. The kit may be dimmed with a standard incandescent dimmer. Ships with 40ft of cable.





### ORDERING INFORMATION

300CBL5P	FINISH	

N MATTE NICKEL

Note: Kits are not customizable.

800CBL5P				
JOB NAME				
NOTES				



# ACCENT CABLE KIT 5 HEAD

## TECH LIGHTING

## **SPECIFICATIONS**

PRIMARY MATERIAL		
SHADE MATERIAL		
NET WEIGHT		
HEIGHT	2.5in	
WIDTH	4in	
LENGTH	12in	
WET LISTED		
DAMP LISTED		
DRY LISTED		
GENERAL LISTING	ETL Listed	
INCLUDES		

### LAMPING SPECIFICATIONS

	LED LAMP	INTEGRATED LED	NON LED	NO LAMP
DELIVERED LUMENS				
WATTS			20	
MAX WATTAGE PER BULB			100W	
INPUT VOLTAGE/ DIMMING TYPE				
CCT				
CRI				
LED LIFETIME				
L70				
AVERAGE BULB HOURS				
FIELD SERVICEABLE LED				
LAMP BASE				
LAMP SHAPE				
LAMP INCLUDED?				
WARRANTY**			1 Year	

 $<sup>* \</sup>texttt{Dimming information available at} \underline{www.techlighting.com/Downloads\#dimming} \\$ 

# T20/T24/JA8 INFORMATION

	Integrated LED	Replacement LED Lamp	No Lamp *
This product can be used to comply with			
California Building Energy Efficiency			N/A
Standards 2016 Title 24 Part 6 / JA8.			
This product can be used to comply with			
California Appliance Efficiency Standards			N1/A
2016 Title 20 and may be shipped to and	d		N/A
sold in California.			

<sup>\*</sup> If a light fixture or component does not include a lamp or light source, it is the responsibility of the customer to select a lamp that meets the T24 and T20 requirements.



<sup>\*\*</sup> Visit techlighting.com for specific warranty limitations and details.