

PRODUCT FEATURES

- Field-changeable optics for ultimate customization
- Advanced LED technology
- Modest size profile to minimize bulky appearance
- Compatible with the Monorail and Monopoint systems by Tech Lighting
- Available in modern finishes
- Protected by a 5-year warranty



LAMPING

Includes 9.2 watt, 647.5 delivered lumens, 2700K or 3000K, 90 CRI field replaceable LED module Dimmable with most LED compatible ELV and Triac dimmers. Choice of 20°, 30° or 40° field changeable optics. Integrated lens holder accommodates up to 2 lenses or louvers (sold separately) As a general rule when using the Brim head, we do not recommend using greater than 33% of the maximum wattage specified for the low voltage transformer due to inrush current requirements. For assistance in calculations, please contact Technical Support. Brim head only compatible with AC transformers. Can use MOCxx Lens.



To view all available finish options, please visit techlighting.com

ORDERING INFORMATION

700	SYSTEM	BRM	COLOR TEMP	BEAM SPREAD	LENGTH (A)	COLOR	FINISH
	FJ FREEJACK		927 90 CRI 2700K	20 20°	05 5"	C CLEAR	B MATTE BLACK
	MP MONOPOINT		930 90 CRI 3000K	30 30°	08 7.76"	K TRANSPARENT SMOKE	S SATIN NICKEL
	MO MONORAIL			40 40°	14 13.76"		

Note: MP includes 4 Round Flush Canopy.
 Matte Black Finish option ships with Satin Nickel Stem.
 4" Stem length not available on WMO System option. For custom stem lengths, please contact the Quotes Department.

700 _____ BRM _____


JOB NAME _____

NOTES _____

BRIM HEAD

SPECIFICATIONS

PRIMARY MATERIAL	Metal
SHADE MATERIAL	
NET WEIGHT	0.79 lbs
HEIGHT	1.3in
WIDTH	3in
LENGTH	3in
BEAM SPREAD	
UP LIGHT / DOWN LIGHT / BOTH?	
WET LISTED	
DAMP LISTED	
DRY LISTED	Yes
MIN. HANGING HEIGHT	4.8in
MAX HANGING HEIGHT	13.8in
TOTAL CORD LENGTH	
SLOPED CEILING ADAPTABLE?	No
GENERAL LISTING	ETL Listed
INCLUDES	



LAMPING SPECIFICATIONS

	LED LAMP	INTEGRATED LED	NON LED	NO LAMP
DELIVERED LUMENS	647.5			
WATTS	9.2			
MAX WATTAGE PER BULB	9.2W			
INPUT VOLTAGE/ DIMMING TYPE	12V ELV 120V ELV			
CCT	Clear, Transparent Smoke : 2700K Clear, Transparent Smoke : 3000K			
CRI	90 CRI			
LED LIFETIME				
L70	>50000			
AVERAGE BULB HOURS	50000			
FIELD SERVICEABLE LED				
LAMP BASE	Integrated LED			
LAMP SHAPE	Integrated LED			
LAMP INCLUDED?	True			
WARRANTY**	5 Years			

* Dimming information available at www.techlighting.com/Downloads#dimming

** Visit techlighting.com for specific warranty limitations and details.

T20 / T24 / JA8 INFORMATION

	Integrated LED	Replacement LED Lamp	No Lamp *
This product can be used to comply with California Building Energy Efficiency Standards 2016 Title 24 Part 6 / JA8.		Yes	
This product can be used to comply with California Appliance Efficiency Standards 2016 Title 20 and may be shipped to and sold in California.		N/A	

* If a light fixture or component does not include a lamp or light source, it is the responsibility of the customer to select a lamp that meets the T24 and T20 requirements.

