PRODUCT FEATURES



LAMPING

Use to secure cables at one end of run (with turnbuckles at other end). Mount to wall or ceiling. 1.5" washer (included) is recommended for ceiling mount support.

Kable Lite Soft Anchors



Kable Lite Soft Anchors

ORDERING INFORMATION

700KSOFT0 FINISH

S SATIN NICKEL

700KSOFT0	
JOB NAME	
NOTES	




KABLE LITE SOFT ANCHORS

TECH LIGHTING

SPECIFICATIONS

PRIMARY MATERIAL		
SHADE MATERIAL		
NET WEIGHT	0.15 lbs	
HEIGHT	1in	
WIDTH	1.5in	
LENGTH	lin	
WET LISTED		
DAMP LISTED		
DRY LISTED		
GENERAL LISTING	ETL Listed	
INCLUDES		



LAMPING SPECIFICATIONS

	LED LAMP	INTEGRATED LED	NON LED	NO LAMP
DELIVERED LUMENS				
WATTS				
MAX WATTAGE PER BULB				
INPUT VOLTAGE/ DIMMING TYPE				
ССТ				
CRI				
LED LIFETIME				
L70				
AVERAGE BULB HOURS				
FIELD SERVICEABLE LED				
LAMP BASE				
LAMP SHAPE				
LAMP INCLUDED?				
WARRANTY**			1 Year	

 $^{* \}texttt{Dimming information available at} \underline{www.techlighting.com/Downloads\#dimming}$

T20/T24/JA8 INFORMATION

	Integrated LED	Replacement LED Lamp	No Lamp *
This product can be used to comply with			
California Building Energy Efficiency			N/A
Standards 2016 Title 24 Part 6 / JA8.			
This product can be used to comply with			
California Appliance Efficiency Standards			N1/A
2016 Title 20 and may be shipped to and	ł		N/A
sold in California.			

^{*} If a light fixture or component does not include a lamp or light source, it is the responsibility of the customer to select a lamp that meets the T24 and T20 requirements.



^{**} Visit techlighting.com for specific warranty limitations and details.