

MONORAIL 4" ROUND POWER FEED CANOPY DUAL-FEED



PRODUCT FEATURES



LAMPING

It brings power to the MonoRail run from a remote transformer (sold separately). The low-voltage leads from the remote transformer are connected to the canopy leads inside the junction box. Isolating connectors are included to isolate power feeds from each other.

MonoRail 4" Round Power Feed Canopy Dual-Feed



MonoRail 4" Round
Power Feed
Canopy Dual-Feed

ORDERING INFORMATION

700MOP4C402 SHAPE OR SIZE

4" ROUND

FINISH

Z ANTIQUE BRONZE

S SATIN NICKEL

700MOP4C402 _____

JOB NAME _____

NOTES _____




MONORAIL 4" ROUND POWER FEED CANOPY DUAL-FEED



SPECIFICATIONS

| | |
|------------------|------------|
| PRIMARY MATERIAL | |
| SHADE MATERIAL | |
| NET WEIGHT | 0.95 lbs |
| HEIGHT | 2.5in |
| WIDTH | 4in |
| LENGTH | 4in |
| WET LISTED | |
| DAMP LISTED | |
| DRY LISTED | |
| GENERAL LISTING | ETL Listed |
| INCLUDES | |



LAMPING SPECIFICATIONS

| | LED LAMP | INTEGRATED LED | NON LED | NO LAMP |
|-----------------------------|----------|----------------|---------|---------|
| DELIVERED LUMENS | | | | |
| WATTS | | | | |
| MAX WATTAGE PER BULB | | | | |
| INPUT VOLTAGE/ DIMMING TYPE | | | | |
| CCT | | | | |
| CRI | | | | |
| LED LIFETIME | | | | |
| L70 | | | | |
| AVERAGE BULB HOURS | | | | |
| FIELD SERVICEABLE LED | | | | |
| LAMP BASE | | | | |
| LAMP SHAPE | | | | |
| LAMP INCLUDED? | | | | |
| WARRANTY** | | | 1 Year | |

* Dimming information available at www.techlighting.com/Downloads#dimming

** Visit techlighting.com for specific warranty limitations and details.

T20 / T24 / JA8 INFORMATION

| | Integrated LED | Replacement LED Lamp | No Lamp * |
|--|----------------|----------------------|-----------|
| This product can be used to comply with California Building Energy Efficiency Standards 2016 Title 24 Part 6 / JA8. | | | N/A |
| This product can be used to comply with California Appliance Efficiency Standards 2016 Title 20 and may be shipped to and sold in California. | | | N/A |

* If a light fixture or component does not include a lamp or light source, it is the responsibility of the customer to select a lamp that meets the T24 and T20 requirements.

