MONORAIL REMOTE KIT 300W

Installs in an accessible location behind the ceiling or wall. Mounts to a standard 4" junction box. Rail drops 2" from ceiling. Add up to six 50 watt elements or up to eight 35 or 37 watt fixture depending on lamp type.

TECH LIGHTING

PRODUCT FEATURES

- (1) 8' long hand bendable MonoRail
- (2) Sets of End Caps

LAMPING

- (1) Power Transformer of your choice
- (2) Individual Rigid Standoffs (lengths will vary)





MonoRail Remote Kit 300w



MonoRail Remote Kit 300w Monorail-Kits End Caps



ORDERING INFORMATION

700MOKTA300 FINISH

R AGED BRASS Z ANTIQUE BRONZE S SATIN NICKEL

700MOKTA300			
JOB NAME			
NOTES			
•			



MONORAIL REMOTE KIT 300W

TECH LIGHTING

SPECIFICATIONS

PRIMARY MATERIAL					
SHADE MATERIAL					
NET WEIGHT					
HEIGHT	20in				
WIDTH	12in				
LENGTH	12in				
WET LISTED					
DAMP LISTED					
DRY LISTED					
GENERAL LISTING	ETL Listed				
INCLUDES					

LAMPING SPECIFICATIONS

	LED LAMP	INTEGRATED LED	NON LED	NO LAMP
DELIVERED LUMENS				
WATTS				
MAX WATTAGE PER BULB			300W	
INPUT VOLTAGE/ DIMMING TYPE			120V ELV	
ССТ				
CRI				
LED LIFETIME				
L70				
AVERAGE BULB HOURS				
FIELD SERVICEABLE LED				
LAMP BASE				
LAMP SHAPE				
LAMP INCLUDED?				
WARRANTY**			1 Year	

 $^{* \ \}mathsf{Dimming} \ \mathsf{information} \ \mathsf{available} \ \mathsf{at} \ \underline{\mathsf{www.techlighting.com/Downloads\#dimming}}$

T20/T24/JA8 INFORMATION

	Integrated LED	Replacement LED Lamp	No Lamp *
This product can be used to comply with California Building Energy Efficiency Standards 2016 Title 24 Part 6 / JA8.			N/A
This product can be used to comply with California Appliance Efficiency Standards 2016 Title 20 and may be shipped to anc sold in California.	ı		N/A

^{*} If a light fixture or component does not include a lamp or light source, it is the responsibility of the customer to select a lamp that meets the T24 and T20 requirements.



^{**} Visit techlighting.com for specific warranty limitations and details.