

PRODUCT FEATURES

- (1) 8' long hand bendable MonoRail
- (2) Sets of End Caps
- (1) Power Transformer of your choice
- (2) Individual Rigid Standoffs (lengths will vary)



LAMPING

Mounts to a standard 4" junction box. Rail drops 1.4" from the ceiling. Add up to (5) 50 watt or (7) 35 watt or 37 watt fixtures depending on lamping type.

Aged Brass



Aged Brass

Antique Bronze

Satin Nickel

ORDERING INFORMATION

700MOMKTS250E FINISH

R AGED BRASS
Z ANTIQUE BRONZE
S SATIN NICKEL

LAMP

-LED LED

700MOMKTS250E _____

JOB NAME _____

NOTES _____



SPECIFICATIONS

PRIMARY MATERIAL	
SHADE MATERIAL	
NET WEIGHT	5 lbs
HEIGHT	1.9in
WIDTH	4in
LENGTH	4in
WET LISTED	
DAMP LISTED	
DRY LISTED	
GENERAL LISTING	ETL Listed
INCLUDES	

LAMPING SPECIFICATIONS

	LED LAMP	INTEGRATED LED	NON LED	NO LAMP
DELIVERED LUMENS				
WATTS				
MAX WATTAGE PER BULB	250W			
INPUT VOLTAGE/ DIMMING TYPE	120V ELV			
CCT				
CRI				
LED LIFETIME				
L70				
AVERAGE BULB HOURS				
FIELD SERVICEABLE LED				
LAMP BASE				
LAMP SHAPE				
LAMP INCLUDED?				
WARRANTY**	1 Year			

* Dimming information available at www.techlighting.com/Downloads#dimming

** Visit techlighting.com for specific warranty limitations and details.

T20 / T24 / JA8 INFORMATION

	Integrated LED	Replacement LED Lamp	No Lamp *
This product can be used to comply with California Building Energy Efficiency Standards 2016 Title 24 Part 6 / JA8.		N/A	
This product can be used to comply with California Appliance Efficiency Standards 2016 Title 20 and may be shipped to and sold in California.		N/A	

* If a light fixture or component does not include a lamp or light source, it is the responsibility of the customer to select a lamp that meets the T24 and T20 requirements.

