

TRAVERSE LOTUS

ROUND 12" FLUSH MOUNT

The Traverse Lotus is a sleek, low-profile flush mount designed for residential and commercial applications. Integrated, high-efficiency LEDs provide even, uniform illumination from edge to edge. This fixture provides a cost-effective solution for applications such as bathrooms, closets, hallways, and much more.


- 90 CRI, 1150 Lumens while only requiring 18-Watts to power
- Complies with CEC 2019 Title 24 Part 6 (JA8-2016, JA8-2019)
- Dimmable. J-Box mounted; can be mounted to ceiling or wall.
- Wet-rated, approved for use in closet storage spaces per NEC Article 410.16
- High-efficiency LEDs; 50,000 life hours



ROUND 12", WHITE

SPECIFICATIONS

DELIVERED LUMENS	1400
WATTS	22
EFFICACY	63
CRI	90+
CCT	3000K
COLOR CONSISTENCY	3-step
INPUT VOLTAGE	120V
DIMMING ¹	10%
CONSTRUCTION	Housing: Polished aluminum Trim: Polyresin
FINISH	White
GENERAL LISTINGS	ETL Listed. Wet-rated. Approved for use in closet storage spaces per NEC Article 410.16
WIRING	6.5" j-box mounted
CALIFORNIA TITLE 24	Registered CEC Appliance Database. Complies with CEC 2019 Title 24 Part 6 (JA8-2016, JA8-2019).
L70	50,000 hours min
WARRANTY ²	5 years



¹See visualcomfort.com for dimmer compatibility.

²Visit visualcomfort.com for specific warranty limitations and details.

ORDERING INFORMATION

FIXTURE

PRODUCT

148212RD-15 TRAVERSE LOTUS, ROUND 12", WHITE

SHIPPING INFORMATION

PACKAGE TYPE	PRODUCT	QTY	UPC	LENGTH	WIDTH	HEIGHT	CUBE	WEIGHT	FREIGHT CLASS	UPS SHIP
INDIVIDUAL	148212RD-15	1	785652073076	12.6"	12.25"	1.75"	0.156	3.35 LBS	65	YES
MASTER PACK	148212RD-15	6	10785652073073	13"	12.6"	12.6"	0.853	21 LBS	65	YES
NJ PALLET		30		48"	40"	70"	77.778	1260 LBS		YES
NV PALLET		360		48"	40"	70"	77.778	1260 LBS		YES

TRAVERSE LOTUS

ROUND 12" FLUSH MOUNT

PROJECT INFORMATION

JOB NAME AND INFORMATION

FIXTURE TYPE AND QUANTITY

NOTES

VISUAL COMFORT & Co.

ARCHITECTURAL COLLECTION

FORMERLY KNOWN AS TECH LIGHTING

7400 Linder Avenue, Skokie, Illinois 60077

T 847.410.4400 | visualcomfort.com

