

VISUAL COMFORT & Co.

14210S-15: 6in Traverse Direct Round T24 3000K 90CRI Dimensions: White



Diameter: 6.62"
Height: 1.12"
Weight: 0.4 lbs.

Wire: 6.5" (color:Black/White)
Mounting Proc.: Key Slots
Connection: Mounted To Box
Bulb Type: Modules
Bulb Type: Integrated
Volts: 120
Watts: 12
Watts Consumed: 12
Watts Rated: 12
Hours Rated: 50000
Lumens: 857
Bulb Temp: 3000 °K
CRI: 90

Bulbs:

1 - LEDIntegrated Modules 12.0w Max. 120v included

Features:

- Meets American with Disabilities Act standard extension requirements
- Product complies with NEC 410.16 code and is closet rated.
- ENERGY STAR® Qualified
- This fixture is classified as a directional light source
- This advanced LED technology is carefully designed and selected to consist of the highest quality LED chipsets for superior performance and reliability.
- Meets Title 24 energy efficiency standards
- Integrated LED fixtures that meet the high efficacy LED standards set forth in Title 24 and are listed in the California Energy Commission Appliance database.

Collection: Traverse Direct

Dimming range: 5%-100%

Featured in the decorative Traverse LED Lyte collection

ENERGY STAR® Qualified

This fixture is classified as a directional light source

This advanced LED technology is carefully designed and selected to consist of the highest quality LED chipsets for superior performance and reliability.

UPC #:785652130557

Finish: White (15)

Material List:

1 Body - Steel - White

Safety Listing:

Safety Listed for Wet Locations

Instruction Sheets:

English (14210S-15)
English (Traverse Direct_142102)

Shade / Glass / Diffuser Details:

Part	Material	Finish	Quantity	Item Number	Length	Width	Height	Diameter	Fitter Diameter	Shade Top Length	Shade Top Width	Shade Top Diameter
Lens	Polycarbonate	Frosted	1	640210-97			0.75	4.38				

Shipping Information:

Package Type	Product #	Quantity	UPC	Length	Width	Height	Cube	Weight	Fr. Class	UPS Ship
Individual	14210S-15	1	785652130557	4.0	4.1	2.1	0.02	0.45	0	Yes
Master Pack		20	10785652130554	14.9	13.0	7.7	0.86	12.0	0	Yes
NJ Pallet		1620		48.0	40.0	77.0	85.56	729.0		No
NV Pallet		1620		48.0	40.0	77.0	85.56	729.0		No