VISUAL COMFORT & CO.

31160EN3-05: Three Light Chandelier





Dimensions:

Diameter: Wire: 144" (color;Clear)

Height: 16.5" Chain: 120'

Weight: 6.2 lbs. Mounting Proc.: Screw Collar -

Chain

Connection: Mounted To Box

Watts: 9 Lumens: 800

Bulbs:

3 - LEDMedium A19 9.0w Max. 120v included

Features:

- · Adjustable arms rotate for up or down lighting
- ENERGY STAR® Qualified
- This fixture features mouth-blown glass and slight variations are an inherent part of the handcrafting process.
- LED Bulbs are an efficient, versatile and durable light source that deliver exceptional performance.
- Meets Title 24 energy efficiency standards
- Title 24 compliant when used with included Joint Appendix (JA8) approved lamp.
- Supplied with wire pre-laced through chain

Material List:

1 Body - Steel - Chrome 1 Chain - Steel - Chrome

Safety Listing:

Safety Listed for Dry Locations

Instruction Sheets:

Trilingual (English, Spanish, and French) (HC-1901FS)

Collection: Oslo

Featured in the decorative Oslo collection

3 A19 Medium 9.3 watt light bulbs

Fixture is supplied with 1 light bulbs

cased opal Etched glass shades

Adjustable arms rotate for up or down lighting

UPC #:785652046469

Finish: Chrome (05)

Shade / Glass / Diffuser Details:

Part	Material	Finish	Quantity	Item Number	Length	Width	Height	Diameter	Fitter Diameter	Shade Top Length	Shade Top Width	Shade Top Diameter
Shade	Glass	Cased Opal Etched	3				5.91	3.94				

Backplate / Canopy Details:

Type	Height / Length	Width	Depth	Diameter	Outlet Box Up	Outlet Box Down
Canopy	0.81			5.5		

Replacement Bulb Data:

Product #		Туре	Base	Watts	Watts Consumed	Volts	Hours	Lumens	Temp (°K)	CRI
-----------	--	------	------	-------	----------------	-------	-------	--------	-----------	-----

Shipping Information:

Package Type	Product #	Quantity	UPC	Length	Width	Height	Cube	Weight	Frt. Class	UPS Ship
Individual	31160EN3-05	1	785652046469	16.5	14.0	9.0	1.2	7.6	0	Yes
Master Pack	31160EN3-05	0	10785652046466							No
NJ Pallet		50		48.0	40.0	76.0	84.44	380.0		No
NV Pallet		50		48.0	40.0	76.0	84.44	380.0		No