

PRODUCT FEATURES

- From the brand formerly known as Tech Lighting
- The LED Driver is housed within the junction box. (2.2" Dia | H. .57")
- Die-cast aluminum structure, powder coat finish, and stainless steel hardware for robust durability in harsh elements. appropriate for commercial use
- Can mount as flush mount on the ceiling or sconce on the wall
- Wet listed, IP65 (International Protection rating indicating resistance to dust and water; suitable and safe for commercial use)
- Ideal for both indoor or outdoor use. Available in modern finishes



LAMPING

Bronze



Bronze

Charcoal

ORDERING INFORMATION

7000WBX	SHAPE OR SIZE	CRI	COLOR TEMP	FINISH	VOLTAGE
	SMALL S	9 90 CRI	30 3000K	Z BRONZE H CHARCOAL	120 120V-277V


7000WBX _____

JOB NAME _____

NOTES _____



SPECIFICATIONS



PRIMARY MATERIAL	Aluminum
SHADE MATERIAL	Glass
NET WEIGHT	5 lbs
HEIGHT	2in
WIDTH	5.3in
LENGTH	5.3in
WET LISTED	
DAMP LISTED	
DRY LISTED	
GENERAL LISTING	ETL Listed
INCLUDES	

LAMPING SPECIFICATIONS

	LED LAMP	INTEGRATED LED	NON LED	NO LAMP
DELIVERED LUMENS		435		
WATTS		12		
MAX WATTAGE PER BULB		Universal 120V-277V ELV, TRIAC		
CCT		3000K		
CRI		90 CRI		
LED LIFETIME		>60000		
AVERAGE BULB HOURS				
FIELD SERVICEABLE LED				
LAMP BASE		Integrated LED		
LAMP SHAPE		Integrated LED		
LAMP INCLUDED?		True		
WARRANTY**		5 Years		

* Dimming information available at www.techlighting.com/Downloads#dimming

** Visit techlighting.com for specific warranty limitations and details.

T20 / T24 / JA8 INFORMATION

	Integrated LED	Replacement LED Lamp	No Lamp *
This product can be used to comply with California Building Energy Efficiency Standards 2016 Title 24 Part 6 / JA8.	Yes		
This product can be used to comply with California Appliance Efficiency Standards 2016 Title 20 and may be shipped to and sold in California.	N/A		

* If a light fixture or component does not include a lamp or light source, it is the responsibility of the customer to select a lamp that meets the T24 and T20 requirements.

